



- Engine: MTU 12V4000G23F
- Alternator: Stamford/Leroy Somer /Hengsheng
- Controller: DeepSea/SmartGen /DEIF/ComAp

Genset

Model	JHM5-1200GF
Voltage	230/400V
Frequency&Speed	50HZ;1500RPM
Genset Prime Power	1300kW/1625kVA
Genset Standby Power	1450kW/1813kVA

Name	12V4000G23F
Application Group	3G
Dataset	Ref. 25°C/45°C

Speed [rpm]	1500
Nominal power [kW]	1420
Nominal power [bhp]	1904
Nominal power [kVA]	-
Nominal power [kWe]	-
Frequency [Hz]	50

Exhaust Regulations China III NRMM compliant (stationary);

Reference conditions

No.	Description	Index	Value	Unit
6	Intake air temperature		25	°C
7	Charge-air coolant temperature		45	°C
8	Barometric pressure		1000	mbar
9	Site altitude above sea level		100	m
10	Raw-water inlet temperature		-	°C

No.	Description	Index	Value	Unit
1	Engine rated speed	A	1500	rpm
2	Reduction gear - Output speed	A	-	rpm
3	Mean piston speed		10.5	m/s
4	Continuous power ISO 3046 (10% overload capability) (design power DIN 6280, ISO 8528)	A	1420	kW
5	Fuel stop power ISO 3046	A	1562	kW
8	Mean effective pressure (MEP) (Continuous power ISO 3046)		19.8	bar
9	Mean effective pressure (MEP) (Fuel stop power ISO 3046)		21.8	bar
18	Performance map No.		-	-
38	Performance map No. (cont.)		-	-
20	Performance map, amendment index		-	-

No.	Description	Index	Value	Unit
1	Naturally aspirated engine		-	-
2	Engine with exhaust turbocharger (ETC)		-	-
3	Engine with exhaust turbocharger (ETC) and intercooler		X	-
4	Exhaust piping, non-cooled		X	-
5	Exhaust piping, liquid-cooled		-	-
33	Working method: four-cycle, diesel, single-acting		X	-
34	Combustion method: direct injection		X	-
36	Cooling system: conditioned water		X	-
37	Direction of rotation: c.c.w. (facing driving end)		X	-
6	Number of cylinders		12	-
7	Cylinder configuration: V angle		90	degrees (°)
8	Cylinder configuration: in-line vertical		-	-
10	Bore		170	mm
11	Stroke		210	mm
12	Displacement, cylinder		4.77	liter
13	Displacement, total		57.2	liter
14	Compression ratio		16.4	-
40	Cylinder heads: single-cylinder		X	-
41	Cylinder liners: wet, replaceable		X	-
42	Piston design: composite piston		-	-
49	Piston design: solid-skirt piston		X	-
21	Number of piston compression rings		2	-
22	Number of piston oil control rings		1	-

Alternator

Pole No.	4-Pole
Exciter Type	Single bearing, Brushless, Self-excited
Power factor	0.8
Voltage adjust range	≅5%
Insulation Grade	H
Protection Grade	IP23/22
Phase / wire	3 phase 4 wires

- ✧ Superior voltage waveform from two-thirds Pitch windings and skewed stator.
- ✧ Digital solid-state.volts-per-hertz voltage Regulator with +1% no-load to full-load regulation.

- ✧ NEMAMG1.JIANGHAO,and ANSI standards compliance for temperature rise and motor starting.
- ✧ Sustained short-circuit current of up to 300% of the rated current for up to 10 seconds.
- ✧ Sustained short-circuit current enabling down stream circuit breakers to trip without collapsing the generator field.
- ✧ Self-ventilated and dripproof construction.

Control Panel



The control module gives digital readouts of:

Generator voltage;
Output frequency;
Engine speed;
Battery voltage;
Engine hours run.

The **control panel** is an Digital Control Module suitable for a wide variety of single, diesel or gas, gen-set applications.

Monitoring an extensive number of engine parameters, the module will display warnings, shutdown and engine status information on the back-lit LCD screen and illuminated LEDs.

The control module has indicators for failure information:

Over speed/Low speed,
Emergency stop
Low oil pressure;
High water temperature
Failure to start
Battery charger failure



Dimension:6100*2200*2700mm
Weight:13000kg



Dimension:12000*2400*2900mm
Weight:16800kg
Fuel Tank Capacity:1000-3000L

Automatic shutdown occurs under:

Low engine oil pressure;
High engine water temperature;
Over speed/Low speed;
Failure to start after three attempts.

Electrical system

- Maintenance-free and anti-explosion battery
- Standard breaker
- ABB breaker (optional)
- ATS (optional)
- Battery charger (optional)
- GMS monitoring (optional)

Packing

- Wrapping film packaging
- Tray packaging
- plywood box packaging

Jiangsu Jianghao Generator Co.,Ltd

Address: No.1 Xixu Road, Medical High-tech Zone,
Taizhou city, Jiangsu, China

Contact Person: Anthony Feng

Email: jhfsale@jhgenerator.com

WhatsApp: +86 18652649673

