



Genset	
Model	JHY5-90GF
Voltage	230/400V
Frequency&Speed	50HZ;1500RPM
Prime Power	90kW/113kVA
Standby Power	99kW/124kVA

➤ **Engine:Yuchai YC4A140Z-D25**

➤ **Alternator:Stamford/Leroy Somer  
/Hengsheng**

➤ **Controller:DeepSea/SmartGen/DEIF  
/ComAp**

**General Engine Data**

No.of Cylinders:	4	Displacement:	4.75L
Bore:	110mm	Lube oil:	13.5L
Stroke:	125mm	Consumption:	205g/kw.h

**Product Features**

- ◆ Electronic unit pump, four-valve structure,turbocharged & intercooled, and Yuchai combustor technologies are adopted for realizing sufficient air intake, full combustion and low fuel consumption, less emission and fast and high-quality loading.
- ◆ High-quality alloy cast iron cylinder block of reinforced grid structure with cambered surface, high-strength vermicular iron cylinder head, dual protection anti-impact cylinder gasket structure, and self-developed cooling technology for the bottom of the cylinder head are adopted, which ensure high reliability.
- ◆ The Yuchai proprietary carbon-scraping self-cleaning technology is adopted for ensuring low Lubricating oil consumption.
- ◆ Electric pre-supply oil technology is adopted, which effectively protects kinematic pair and improves the service life of engine.
- ◆ The crankshaft is made of high-quality alloy steel by using all fiber extrusion forging process, and the journal and circular bead are subject to quenching heat treatment for improving wear resistance and prolonging service life.
- ◆ The structure of one head for one cylinder is adopted; maintenance window is set at the side of the engine body, which ensures easy maintenance.

**Alternator**

Pole No.	4-Pole
Exciter Type	Single bearing, Brushless, Self-excited
Power factor	0.8
Voltage adjust range	≅ 5%
Insulation Grade	H
Protection Grade	IP23/22
Phase / wire	3 phase 4 wires

- ✧ NEMAMG1.JIANGHAO,and ANSI standards compliance for temperature rise and motor starting.
- ✧ Sustained short-circuit current of up to 300% of the rated current for up to 10 seconds.
- ✧ Sustained short-circuit current enabling down stream circuit breakers to trip without collapsing thegenerator field.
- ✧ Self-ventilated and dripproof construction.
- ✧ Superior voltage waveform from two-thirds pitch windings and skewed stator.
- ✧ Digital solid-state.volts-per-hertz voltage regulator with +1% no-load to full-load regulation.

## Control Panel



The control module gives digital readouts of:

Generator voltage;  
Output frequency;  
Engine speed;  
Battery voltage;  
Engine hours run.

The **control panel** is an Digital Control Module suitable for a wide variety of single, diesel or gas, gen-set applications.

Monitoring an extensive number of engine parameters, the module will display warnings, shutdown and engine status information on the back-lit LCD screen and illuminated LEDs.

**The control module has indicators for failure information:**

Over speed/Low speed,  
Emergency stop  
Low oil pressure;  
High water temperature  
Failure to start  
Battery charger failure



Dimension:2080\*940\*1390mm  
Weight:1250kg

**Automatic shutdown occurs under:**

Low engine oil pressure;  
High engine water temperature;  
Over speed/Low speed;  
Failure to start after three attempts.

## Electrical system

- Maintenance-free and anti-explosion battery
- Standard breaker
- ABB breaker (optional)
- ATS (optional)
- Battery charger (optional)
- GMS monitoring (optional)

## Packing

- Wrapping film packaging
- Tray packaging
- plywood box packaging



Dimension:3300\*1300\*1800mm  
Weight:2300kg  
Fuel Tank Capacity:360L

**Jiangsu Jianghao Generator Co.,Ltd**

Address: No.1 Xixu Road, Medical High-tech Zone,  
Taizhou city, Jiangsu, China

Contact Person: Anthony Feng

Email: [jhfsale@jhgenerator.com](mailto:jhfsale@jhgenerator.com)

WhatsApp: +86 18652649673

